

## DATASHEET

PART NUMBER

### WES397-SIN-TS

**Wescon 397 Stainless Steel Microstop - 1/4-28  
- 7/16" Cutter Capacity - Slotted Internal  
Thread Skirt - Nylon Foot**

SMALL CAPACITY / TIGHT SPACE APPLICATIONS  
STAINLESS STEEL

WEBSITE

<https://www.wesconusa.com/products/WES397-SIN-TS>



\* The image represents the general look of the series. Actual product may vary based on options selected.

## SPECIFICATIONS

<b>Measurement Type</b>	Imperial
<b>Bearing Rating</b>	10,000 rpm
<b>Bearing Type</b>	Dual Ball Bearings
<b>Heavy Duty Thrust Bearing</b>	No
<b>Incremental Adjustment</b>	0.0005 in
<b>Shaft Travel</b>	0.15 in
<b>Cutter Thread</b>	1/4-28
<b>Shaft</b>	Threaded Shank (1/4-28)
<b>Shaft Diameter</b>	1/4 in
<b>Cutter Capacity</b>	7/16 in
<b>Skirt</b>	Slotted Internal Thread
<b>Skirt Description</b>	7/16 in Cutter Capacity
<b>Foot</b>	Nylon
<b>Solid Stop</b>	Yes
<b>Material</b>	Stainless Steel
<b>Stroke Length</b>	0.157 in (4mm) Shaft Travel
<b>Country of Origin</b>	USA

**ADDITIONAL IMAGES AND DRAWINGS**



Image 0

### WES397 Series Microstop



**Part Number**  
WES397-X-XX-XX-XX

- Shaft Option
- Foot Style
- Skirt Option\*
- Cutter Thread
- Shaft Travel

Code	Shaft Travel
(Blank)	0.157in
ES	0.246in


Code	Cutter Thread
(Blank)	1/4-28
6	M6x1

Code	Foot Style
N	Nylon

Code	Shaft Option
(Blank)	1/4in Standard Round
TF	Tri Flat
QC	Quick Change
TS	1/4-28in Threaded Shank

Incremental Adjustment: 0.0005 in  
Material: Stainless Steel

Bearing Rating: 10,000 rpm  
Bearing Type: Dual Ball-Bearings  
Dust Seal: Integrated Dust Seal  
Heavy Duty Thrust Bearing: No  
Solid Stop: Yes



\*For Skirt options see next page and website.



Part Number

**WES397**

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.  
601 Century Plaza Dr. Houston, TX 77073, US  
www.wesconusa.com

Wescon 397 Microstop


Revision 04

All dimensions are in inches


Information in this drawing is provided for reference only

Image 1


**Skirt Option**



**S**  
Straight  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)




**I**  
Internal Thread  
Cutter  $\frac{7}{16}$ " ( $\varnothing$ 11mm)  
Choose Foot Style From Table



**E**  
External Thread  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)  
Choose Foot Style From Table




**SL**  
Slotted  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)




**SI**  
Slotted Internal Thread  
Cutter  $\frac{7}{16}$ " ( $\varnothing$ 11mm)  
Choose Foot Style From Table




**SE**  
Slotted External Thread  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)  
Choose Foot Style From Table



**SCA**  
Straight Cutaway  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)




**S2L**  
2-Leg  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)




**S3L**  
3-Leg  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)



**WVS**  
Vacuum Straight  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)



**WVI**  
Vacuum Internal Thread  
Cutter  $\frac{7}{16}$ " ( $\varnothing$ 11mm)  
Choose Foot Style From Table



**WVE**  
Vacuum External Thread  
Cutter  $\frac{1}{2}$ " ( $\varnothing$ 12mm)  
Choose Foot Style From Table



Part Number

**WES397**

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.  
601 Century Plaza Dr. Houston, TX 77073, US  
www.wesconusa.com

Wescon 397 Microstop

Revision 05

All dimensions are in inches

Information in this drawing is provided for reference only

Image 2

**Foot Style  
For External Thread**



Part Number	Material
39631-N	Nylon
39631-S	Steel
39631-P	Phenolic

**Foot Style  
For Internal Thread**



Part Number	Material
39620-N	Nylon
39620-S	Steel
39620-P	Phenolic



Part Number	<b>WES397</b>
-------------	---------------

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.  
601 Century Plaza Dr. Houston, TX 77073, US  
www.wesconusa.com

Wescon 397 Microstop

Revision 05	All dimensions are in Inches	Information in this drawing is provided for reference only
-------------	------------------------------	--

Image 3