Wescon Industries Inc.
601 Century Plaza Dr, Houston, TX 77073
www.wesconusa.com

# DATASHEET

PART NUMBER

# WES596-8-FH-QC

## Wescon 596 Microstop - M8x1 - 19 mm Cutter Capacity - Flanged High

HIGH SPEED HEAVY DUTY

WEBSITE

https://www.wesconusa.com/products/WES596-8-FH-QC

* The image represents the general look of the series. Actual product may vary based on options selected.

## SPECIFICATIONS

| | |
|---|---|
| **Measurement Type** | Metric |
| **Bearing Rating** | 10,000 rpm |
| **Bearing Type** | Dual Ball Bearings |
| **Heavy Duty Thrust Bearing** | Yes |
| **Incremental Adjustment** | 0.013 mm |
| **Shaft Travel** | 7.60 mm |
| **Dust Seal** | Integrated Dust Seal |
| **Cutter Thread** | M8x1 |
| **Shaft** | Quick Change |
| **Shaft Diameter** | 6.35 mm |
| **Cutter Capacity** | 19 mm |
| **Skirt** | Flanged High |
| **Skirt Description** | 30 mm OD 19 mm Cutter Capacity |
| **Solid Stop** | Yes |
| **Material** | Steel |
| **Country of Origin** | USA |



Subject to change without notice
© Copyright Wescon Industries Inc

## ADDITIONAL IMAGES AND DRAWINGS

### WES596 Series Microstop

**Part Number**
WES596-X-XX-XX

- Shaft Option
- Foot Style
- Skirt Option*
- Cutter Thread

Incremental Adjustment: 0.0005 in
Shaft Travel: 0.300 in
Material: Carbon Steel Body with Hardened Tool Steel Shaft

Bearing Rating: 10,000 rpm
Bearing Type: Dual Ball-Bearings
Dust Seal: Integrated Dust Seal
Heavy Duty Thrust Bearing: Yes
Solid Stop: Yes

| Code | Cutter Thread |
|---|---|
| (Blank) | 1/4-28 |
| 6 | M6x1 |
| 8 | M8x1 |

| Code | Foot Style |
|---|---|
| N | Nylon |
| S | Steel |
| P | Phenolic |

| Code | Shaft Option |
|---|---|
| (Blank) | 1/4" Standard Round |
| QC | Quick Change |
| TF | Tri Flat |
| TSL | 1/4-28 Threaded Shank Long |




**WES596-S**
Microstop with
Ø1/4" Standard Shaft




**WES596-SL-TF**
Microstop with
Tri-Flat Shaft




**WES596-SCA-TSL**
Microstop with
1/4-28 Threaded Shank Long Shaft




**WES596-S3L-QC**
Microstop with
Quick Change shaft

*For Skirt options see next page and website.

WESCON

Part Number
**WES596**

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.
601 Century Plaza Dr. Houston, TX 77073, US
www.wesconusa.com

Wescon 596 Microstop

Revision 09 | All dimensions are in Inches | Information in this drawing is provided for reference only

Image 1


Subject to change without notice
© Copyright Wescon Industries Inc

## Skirt Option




**S**
Straight
Cutter Ø3/4"(Ø19mm)




**I**
Internal Thread*
Cutter Ø5/8"(Ø15mm)




**E**
External Thread*
Cutter Ø3/4"(Ø19mm)




**SCA**
Straight Cutaway
Cutter Ø3/4"(Ø19mm)




**SL**
Slotted
Cutter Ø3/4"(Ø19mm)




**SI**
Slotted Internal Thread*
Cutter Ø5/8"(Ø15mm)




**SE**
Slotted External Thread*
Cutter Ø3/4"(Ø19mm)




**SSCA**
Slotted Straight Cutaway
Cutter Ø3/4"(Ø19mm)




**B**
Bell
Cutter Ø7/8" (Ø22mm)




**BI**
Bell Internal Thread*
Cutter Ø3/4"(Ø19mm)




**BE**
Bell External Thread*
Cutter Ø7/8"(Ø22mm)




**FCA**
Flanged Cutaway
Cutter Ø3/4"(Ø19mm)




**SBI**
Slotted Bell Internal Thread*
Cutter Ø3/4"(Ø19mm)




**SBE**
Slotted Bell External Thread*
Cutter Ø7/8"(Ø22mm)




**BWE**
Bell Wide External Thread*
Cutter Ø1"(Ø25mm)




**S-875**
Straight 0.875 in OD
Cutter Ø5/8"(Ø15mm)

*Select foot style from table
Continued In Next Page.

WESCON

Part Number **WES596**

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.
601 Century Plaza Dr. Houston, TX 77073, US
www.wesconusa.com

Wescon 596 Microstop

Revision 09 | All dimensions are in Inches | Information in this drawing is provided for reference only

Image 2



Subject to change without notice
© Copyright Wescon Industries Inc

## Skirt Option (Continuation)




**F**
Flanged
Cutter Ø3/4"(Ø19mm)




**FH**
Flanged High
Cutter Ø3/4" (Ø19mm)




**SF**
Spherical Flanged
Cutter Ø3/4" (Ø19mm)




**F-1125**
Flanged 1.125 in OD
Cutter Ø3/4"(Ø19mm)




**C**
Close Quarters
Cutter Ø3/8"(Ø10mm)




**F2L**
Flanged 2-Leg
Cutter Ø3/4"(Ø19mm)




**S2L**
2-Leg
Cutter Ø3/4"(Ø19mm)




**S3L**
3-Leg
Cutter Ø3/4"(Ø19mm)




**WVI**
Vaccuum Internal Thread*
Cutter Ø5/8"(Ø15mm)




**WVE**
Vaccuum External Thread*
Cutter Ø3/4"(Ø19mm)




**SVI**
Slotted Vaccuum Internal Thread*
Cutter Ø5/8"(Ø15mm)




**SVE**
Slotted Vaccuum External Thread*
Cutter Ø3/4"(Ø19mm)




**WVS**
Vaccuum Straight
Cutter Ø3/4"(Ø19mm)




**SVS**
Slotted Vaccuum Straight
Cutter Ø3/4"(Ø19mm)

*Select foot style from table

WESCON

Part Number **WES596**

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.
601 Century Plaza Dr. Houston, TX 77073, US
www.wesconusa.com

Wescon 596 Microstop

Revision 09 | All dimensions are in Inches | Information in this drawing is provided for reference only

Image 3


Subject to change without notice
© Copyright Wescon Industries Inc

## Skirt Option




**VS**
Vaccuum Straight
Cutter Ø3/4"(Ø19mm)




**VE**
Vaccuum External Thread*
Cutter Ø3/4"(Ø19mm)




**VI**
Vaccuum Internal Thread*
Cutter Ø5/8"(Ø15mm)




| Part Number | Material |
|---|---|
| 59631-N | Nylon |
| 59631-S | Steel |
| 59631-P | Phenolic |

**Foot Style For External Thread**




| Part Number | Material |
|---|---|
| 59620-N | Nylon |
| 59620-S | Steel |
| 59620-P | Phenolic |

**Foot Style For Internal Thread**




| Part Number | Material |
|---|---|
| 59641-N | Nylon |
| 59641-S | Steel |
| 59641-P | Phenolic |

**Foot Style For Bell External Thread**




| Part Number | Material |
|---|---|
| 59640-N | Nylon |
| 59640-S | Steel |
| 59640-P | Phenolic |

**Foot Style For Bell Internal Thread**




| Part Number | Material |
|---|---|
| 59651-N | Nylon |
| 59651-S | Steel |
| 59651-P | Phenolic |

**Foot Style For Bell Wide External Thread**

*Select foot style from table

WESCON

Part Number **WES596**

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.
601 Century Plaza Dr. Houston, TX 77073, US
www.wesconusa.com

Wescon 596 Microstop

Revision 09 | All dimensions are in Inches | Information in this drawing is provided for reference only

Image 4


Subject to change without notice
© Copyright Wescon Industries Inc