

DATASHEET

PART NUMBER

WES596-ER6

Wescon 596-ER Extended Reach - 1/4-28 - 5/8"
Cutter Capacity - 2.75 in Length 5/8 in Cutter Capacity

EXTENDED REACH UNITS

WEBSITE

<https://www.wesconusa.com/products/WES596-ER6>



SPECIFICATIONS


Measurement Type	Imperial
Bearing Rating	10,000 rpm
Bearing Type	Dual Ball Bearings
Heavy Duty Thrust Bearing	Yes
Incremental Adjustment	0.0005 in
Shaft Travel	0.300 in
Dust Seal	Integrated Dust Seal
Cutter Thread	1/4-28
Shaft	Round
Shaft Diameter	1/4 in
Cutter Capacity	5/8 in
Skirt	2.75 in Length 5/8 in Cutter Capacity
Skirt Length	2.75 in
Skirt Description	0.750 in OD 5/8 in Cutter Capacity
Solid Stop	Yes
Material	Steel
Country of Origin	USA

ADDITIONAL IMAGES AND DRAWINGS

WES596 Extended Reach Series Microstop



Part Number
WES596-X-XX-XX



Code	Shaft Option
(Blank)	1/4in standard Round
QC	Quick Change
TF	Tri Flat

Skirt Option	A (Skirt Length)	Ø B (O.D)	Ø C (I.D)	Cutter Capacity	Cutter Thread
ER1	6.00"(152.4mm)	0.68"(17.4mm)	0.55"(13.9mm)	Ø 1/2"(Ø 12.7mm)	1/4-28
ER3	4.50"(114.3mm)	0.50"(12.7mm)	0.40"(10.1mm)	Ø 3/8"(Ø 9.52mm)	1/4-28
ER5	6.00"(152.4mm)	0.50"(12.7mm)	0.40"(10.1mm)	Ø 3/8"(Ø 9.52mm)	1/4-28
ER8	6.00"(152.4mm)	0.37"(9.52mm)	0.27"(6.98mm)	Ø 1/4"(Ø 6.35mm)	10-32
ER9	6.00"(152.4mm)	0.42"(10.7mm)	0.32"(8.25mm)	Ø 5/16"(Ø 7.94mm)	1/4-28
ER14	8.00"(203.2mm)	0.68"(17.4mm)	0.53"(13.4mm)	Ø 1/2"(Ø 12.7mm)	1/4-28

*Metric M6x1 thread also available

Incremental Adjustment: 0.0005 in
Shaft Travel: 0.300 in
Material: Carbon Steel Body with
Hardened Tool Steel Shaft


Bearing Rating: 10,000 rpm
Bearing Type: Dual Ball-Bearings
Dust Seal: Integrated Dust Seal
Heavy Duty Thrust Bearing: Yes
Solid Stop: Yes



ER3



ER8



ER14
Slotted



Part Number

WES596-ER

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

© 2025 Wescon Industries Inc.
601 Century Plaza Dr. Houston, TX 77073, US
www.wesconusa.com

Revision 04

All dimensions are in Inches

Information in this drawing is provided for reference only

Wescon 596 Extended Reach
Microstop

Image 1