

## DATASHEET

### PART NUMBER

### **WES597-6-SIP**

**Wescon 597 Stainless Steel Microstop - M6x1 -  
 15 mm Cutter Capacity - Slotted Internal  
 Thread Skirt - Phenolic Foot**

HIGH SPEED HEAVY DUTY STAINLESS STEEL

### WEBSITE

<https://www.wesconusa.com/products/WES597-6-SIP>




\* The image represents the general look of the series. Actual product may vary based on options selected.

### SPECIFICATIONS

<b>Measurement Type</b>	Metric
<b>Bearing Rating</b>	10,000 rpm
<b>Bearing Type</b>	Dual Ball Bearings
<b>Heavy Duty Thrust Bearing</b>	Yes
<b>Incremental Adjustment</b>	0.013 mm
<b>Shaft Travel</b>	7.60 mm
<b>Dust Seal</b>	Integrated Dust Seal
<b>Cutter Thread</b>	M6x1
<b>Shaft</b>	Round
<b>Shaft Diameter</b>	6.35 mm
<b>Cutter Capacity</b>	15 mm
<b>Skirt</b>	Slotted Internal Thread
<b>Skirt Description</b>	25.4 mm OD 15 mm Cutter Capacity
<b>Foot</b>	Phenolic
<b>Solid Stop</b>	Yes
<b>Material</b>	Stainless Steel
<b>Country of Origin</b>	USA

## ADDITIONAL IMAGES AND DRAWINGS

**WES597 SERIES MICROSTOP**



**Part Number**  
WES597-X-XX-XX


Shaft Option  
Foot Style  
Skirt Option\*  
Cutter Thread

Code	Cutter Thread
(Blank)	1/4-28
6	M6x1
8	M8x1

Code	Shaft Option
(Blank)	1/4in Standard Round
-QC	Quick Change
-TF	Tri Flat
-TSL	1/4-28in Threaded Shank Long

Incremental Adjustment: 0.0005 in  
Shaft Travel: 0.300 in  
Material: Stainless Steel

Bearing Rating: 10,000 rpm  
Bearing Type: Dual Ball-Bearings  
Dust Seal: Integrated Dust Seal  
Heavy Duty Thrust Bearing: Yes  
Solid Stop: Yes



\*For Skirt options see next page and website.

 **WESCON**

Part Number **WES597**

Wescon 597 Microstop

Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.

All dimensions are in Inches

© 2025 Wescon Industries Inc.  
601 Century Plaza Dr, Houston, TX 77073, US  
[www.wesconusa.com](http://www.wesconusa.com)

Information in this drawing is provided for reference only

Image 1






Image 2


### Skirt Option (Continuation)




**VI**  
Vacuum Internal  
Thread  
Cutter  $\phi 5/8"$  ( $\phi 15mm$ )



**VE**  
Vacuum External  
Thread  
Cutter  $\phi 3/4"$  ( $\phi 19mm$ )



**SVI**  
Slotted Vacuum External  
Thread  
Cutter  $\phi 5/8"$  ( $\phi 15mm$ )




**SVE**  
Slotted Vacuum External  
Thread  
Cutter  $\phi 3/4"$  ( $\phi 19mm$ )

 <b>WESCON</b>	Part Number <b>WES597</b>
Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.  All dimensions are in Inches	© 2025 Wescon Industries Inc. 601 Century Plaza Dr, Houston, TX 77073, US <a href="http://www.wesconusa.com">www.wesconusa.com</a>  Information in this drawing is provided for reference only
	Wescon 597 Microstop

Image 3

**Foot Style  
For External Thread**




Part Number	Material
59631-N	Nylon
59631-S	Steel
59631-P	Phenolic

**Foot Style  
For Internal Thread**




Part Number	Material
59620-N	Nylon
59620-S	Steel
59620-P	Phenolic

**Foot Style  
For Bell External Thread**



Part Number	Material
59641-N	Nylon
59641-S	Steel
59641-P	Phenolic

**Foot Style  
For Bell Internal Thread**



Part Number	Material
59640-N	Nylon
59640-S	Steel
59640-P	Phenolic



Part Number

**WES597**

Do not modify, copy,  
distribute, or reproduce  
this drawing without prior  
written authorization.

© 2025 Wescon Industries Inc.  
601 Century Plaza Dr, Houston, TX 77073, US  
www.wesconusa.com

All dimensions are in Inches

Information in this drawing is provided for reference only

Wescon 597 Microstop

Image 4