

DATASHEET

PART NUMBER

WES597-SEP

Wescon 597 Stainless Steel - 1/4-28 - 3/4"
Cutter Capacity - Slotted External Thread Skirt
- Phenolic Foot

HIGH SPEED HEAVY DUTY STAINLESS STEEL

WEBSITE

<https://www.wesconusa.com/products/WES597-SEP>




* The image represents the general look of the series. Actual product may vary based on options selected.

SPECIFICATIONS

Measurement Type	Imperial
Bearing Rating	10,000 rpm
Bearing Type	Dual Ball Bearings
Heavy Duty Thrust Bearing	Yes
Incremental Adjustment	0.0005 in
Shaft Travel	0.300 in
Dust Seal	Integrated Dust Seal
Cutter Thread	1/4-28
Shaft	Round
Shaft Diameter	1/4 in
Cutter Capacity	3/4 in
Skirt	Slotted External Thread
Skirt Description	1-1/4 in OD 3/4 in Cutter Capacity
Foot	Phenolic
Solid Stop	Yes
Material	Stainless Steel
Country of Origin	USA

ADDITIONAL IMAGES AND DRAWINGS



Part Number
WES596-XX-XX


Shaft Option
Foot Style
(For Skirts I.SI, E.SE, BI, SBI,
BE, SBE, VI, BVI, BVE)
Skirt Option*

Code	Shaft Option
(Blank)	Round
-QC	Quick Change
-TF	Tri Flat
-TSL	Threaded Shank Long

Code	Foot Style
N	Nylon
S	Steel
P	Phenolic

Incremental Adjustment: 0.0005 in
Shaft Travel: 0.300 in
Cutter Thread: 1/4-28
Material: Stainless Steel

Bearing Rating: 10,000 rpm
Bearing Type: Dual Ball-Bearings
Dust Seal: Integrated Dust Seal
Heavy Duty Thrust Bearing: Yes
Solid Stop: Yes




(Shaft Option)

3.65in Ref.

(Skirt Option)

Ø 1.10in

**WESCON**

© 2025 Wescon Industries Inc.
601 Century Plaza Dr. Houston, TX 77073, US
www.wesconusa.com

Part Number
WES597

Wescon 597 Microstop

*For Skirt options see next page and website.

All dimensions are in inches

Information in this drawing is provided for reference only

Image 1




Image 2