

DATASHEET

PART NUMBER

WES598-6-F-1125-TF

**Wescon 598 Microstop - M6x1 - 19 mm Cutter
Capacity - Flanged 1.125 in OD Skirt**

10 DEGREE PIVOTING SHAFT (SWIVEL SHAFT) / HIGH
SPEED HEAVY DUTY

WEBSITE

<https://www.wesconusa.com/products/WES598-6-F-1125-TF>



* The image represents the general look of the series. Actual product may vary based on options selected.

SPECIFICATIONS

Measurement Type	Metric
Bearing Rating	10,000 rpm
Bearing Type	Dual Ball Bearings
Heavy Duty Thrust Bearing	Yes
Incremental Adjustment	0.013 mm
Shaft Travel	7.60 mm
Dust Seal	Integrated Dust Seal
Cutter Thread	M6x1
Shaft	Tri-Flat - Pivoting / Swivel Shaft
Shaft Diameter	6.35 mm
Cutter Capacity	19 mm
Skirt	Flanged 1.125 in OD
Skirt Description	28.58 mm OD 19 mm Cutter Capacity
Solid Stop	Yes
Material	Steel
Country of Origin	USA

ADDITIONAL IMAGES AND DRAWINGS

Part Number
WES598-X-XX-XX

- Shaft Option
- Foot Style
- Skirt Option*
- Cutter Thread

Code	Cutter Thread	Code	Shaft Option	Code	Foot Style
(Blank)	1/4-28	(Blank)	Round Swivel Shaft	N	Nylon
6	M6x1	-QC	Quick Change Swivel Shaft	S	Steel
8	M8x1	-TF	Tri Flat Swivel Shaft	P	Phenolic

Incremental Adjustment: 0.0005 in
Shaft Travel: 0.300 in

Bearing Rating: 10,000 rpm
Bearing Type: Dual Ball-Bearings
Dust Seal: Integrated Dust Seal
Heavy Duty Thrust Bearing: Yes
Solid Stop: Yes

3.96in Ref.

5°

5°

(Shaft Option)

(Skirt Option)

∅ 1.00in

WESCON USA

<p>© 2025 Wescon Industries Inc. 601 Century Plaza Dr. Houston, TX 77073, US www.wesconusa.com</p>	Part Number WES598
	Wescon 598 Microstop











*For Skirt options see next page and website.

All dimensions are in inches

Information in this drawing is provided for reference only

Image 1

Skirt Option



 © 2025 Wescon Industries Inc. 601 Century Plaza Dr. Houston, TX 77073, US www.wesconusa.com	Part Number WES598
	Wescon 598 Microstop

All dimensions are in inches Information in this drawing is provided for reference only

Image 2