

DATASHEET

PART NUMBER

WES598-6-SBEN-TF

Wescon 598 Microstop - M6x1 - 22 mm Cutter Capacity - Slotted Bell External Thread Skirt - Nylon Foot

10 DEGREE PIVOTING SHAFT (SWIVEL SHAFT) / HIGH SPEED HEAVY DUTY

WEBSITE

<https://www.wesconusa.com/products/WES598-6-SBEN-TF>



* The image represents the general look of the series. Actual product may vary based on options selected.

SPECIFICATIONS

Measurement Type	Metric
Bearing Rating	10,000 rpm
Bearing Type	Dual Ball Bearings
Heavy Duty Thrust Bearing	Yes
Incremental Adjustment	0.013 mm
Shaft Travel	7.60 mm
Dust Seal	Integrated Dust Seal
Cutter Thread	M6x1
Shaft	Tri-Flat - Pivoting / Swivel Shaft
Shaft Diameter	6.35 mm
Cutter Capacity	22 mm
Skirt	Slotted Bell External Thread
Skirt Description	35.5 mm OD 22 mm Cutter Capacity
Foot	Nylon
Solid Stop	Yes
Material	Steel
Country of Origin	USA

ADDITIONAL IMAGES AND DRAWINGS

WES598 Series Microstop

Part Number
WES598-X-XX-XX



WESCON USA

Code | Cutter Thread

(Blank)	1/4-28
6	M6x1
8	M8x1

Code | Foot Style

N	Nylon
S	Steel
P	Phenolic

Shaft Option
Foot Style
Skirt Option*
Cutter Thread

Code | Shaft Option

(Blank)	Round Swivel Shaft
-QC	Quick Change Swivel Shaft
-TF	Tri Flat Swivel Shaft

5°

3.96in Ref.

5°

(Shaft Option)

(Skirt Option)

∅ 1.00in

Incremental Adjustment: 0.0005 in
Shaft Travel: 0.300 in
Material: Hardened Steel With Black Oxide Finish


Bearing Rating: 10,000 rpm
Bearing Type: Dual Ball-Bearings
Dust Seal: Integrated Dust Seal
Heavy Duty Thrust Bearing: Yes
Solid Stop: Yes

*For Skirt options see next page and website.


 WESCON	Part Number WES598	Wescon 598 Microstop
<p>Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.</p> <p>All dimensions are in Inches</p>		<p>© 2025 Wescon Industries Inc. 601 Century Plaza Dr, Houston, TX 77073, US www.wesconusa.com</p> <p>Information in this drawing is provided for reference only</p>

Image 1


Skirt Option (Continuation)




VI
Vacuum Internal
Thread
Cutter $\phi 5/8"$ ($\phi 15mm$)



VE
Vacuum External
Thread
Cutter $\phi 3/4"$ ($\phi 19mm$)



SVI
Slotted Vacuum External
Thread
Cutter $\phi 5/8"$ ($\phi 15mm$)



SVE
Slotted Vacuum External
Thread
Cutter $\phi 3/4"$ ($\phi 19mm$)

 WESCON <small>Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.</small> <small>All dimensions are in Inches</small>	<small>© 2025 Wescon Industries Inc. 601 Century Plaza Dr, Houston, TX 77073, US www.wesconusa.com</small> <small>Information in this drawing is provided for reference only</small>	<small>Part Number</small> WES598 Wescon 598 Microstop
--	---	--


Image 2

Skirt Option				
S Straight Cutter $\phi 3/4"$ ($\phi 19mm$)	S2L 2-Leg Cutter $\phi 3/4"$ ($\phi 19mm$)	S3L 3-Leg Cutter $\phi 3/4"$ ($\phi 19mm$)	SL Slotted Cutter $\phi 3/4"$ ($\phi 19mm$)	F Flanged Cutter $\phi 3/4"$ ($\phi 19mm$)
SI Slotted Internal Thread Cutter $\phi 5/8"$ ($\phi 15mm$)	I Internal Thread Cutter $\phi 5/8"$ ($\phi 15mm$)	E External Thread Cutter $\phi 3/4"$ ($\phi 19mm$)	SE Slotted External Thread Cutter $\phi 3/4"$ ($\phi 19mm$)	B Bell Cutter $\phi 7/8"$ ($\phi 22mm$)
SCA Straight Cutaway Cutter $\phi 3/4"$ ($\phi 19mm$)	SBE Slotted Bell External Thread Cutter $\phi 7/8"$ ($\phi 22mm$)	BE Bell External Thread Cutter $\phi 7/8"$ ($\phi 22mm$)	SBI Slotted Bell Internal Thread Cutter $\phi 3/4"$ ($\phi 19mm$)	BI Bell Internal Thread Cutter $\phi 3/4"$ ($\phi 19mm$)
FCA Flanged Cutaway Cutter $\phi 3/4"$ ($\phi 19mm$)	F2L Flanged 2-Leg Cutter $\phi 3/4"$ ($\phi 19mm$)	C Close Quarters Cutter $\phi 3/8"$ ($\phi 10mm$)	SSCA Slotted Straight Cutaway Cutter $\phi 3/4"$ ($\phi 19mm$)	
<div style="display: flex; align-items: center;"> WESCON </div>		Part Number WES598		
<small>Do not modify, copy, distribute, or reproduce this drawing without prior written authorization.</small> <small>All dimensions are in Inches</small>		<small>© 2025 Wescon Industries Inc. 601 Century Plaza Dr, Houston, TX 77073, US www.wesconusa.com</small> <small>Information in this drawing is provided for reference only</small>	Wescon 598 Microstop	

Continued In Next Page


Image 3

**Foot Style
For External Thread**




Part Number	Material
59631-N	Nylon
59631-S	Steel
59361-P	Phenolic

**Foot Style
For Internal Thread**




Part Number	Material
59620-N	Nylon
59620-S	Steel
59620-P	Phenolic

**Foot Style
For Bell External Thread**



Part Number	Material
59641-N	Nylon
59641-S	Steel
59641-P	Phenolic

**Foot Style
For Bell Internal Thread**



Part Number	Material
59640-N	Nylon
59640-S	Steel
59640-P	Phenolic



Part Number

WES598

Do not modify, copy,
distribute, or reproduce
this drawing without prior
written authorization.

© 2025 Wescon Industries Inc.
601 Century Plaza Dr, Houston, TX 77073, US
www.wesconusa.com

All dimensions are in Inches

Information in this drawing is provided for reference only

Wescon 598 Microstop

Image 4